



OILCORP

PRODUCT DATA SHEET

OC DEX III AUTO TRANS FLUID

Automatic Transmission Fluid

Product Description

OC DEX III AUTO TRANS FLUID is a premium quality fluid blended for use in automatic transmissions requiring the use of DEXRON® III specification fluids. This product is a high viscosity index fluid containing superior anti-wear protection, oxidation control and friction performance which provides exceptional thermal stability as well as oxidation resistance and sludge control.

Applications

OC DEX III AUTO TRANS FLUID is suitable for:

- Allison C-4 Fluids
- Allison TES, 389
- Caterpillar TO-2 Fluids
- Chrysler transmissions (except where Chrysler MS-9602 or MS- 176 is required).
- Ford MERCON®
- Ford M2C138-CJ, M2C 166-H Fluids.
- GM DEXRON® III-H, III-G, III-F, III-E, III-D.
- MAN 339 Z1 & V1, Z2 & V2.
- MB 236.1, 236.5, 236.6, 236.7
- Voith 55,6335 & 55,6336
- Volvo 97340, 97341.
- ZF TE-ML 02F, 04D, 09, 11A, 14A, 17C.

DEXRON® is a registered trademark of General Motors Corporation. MERCON® is a registered trade mark of Ford Motor Company.

Packaging

205L, 20L, 5L, 1L

Typical Physical Characteristics

Property	Typical Value
Density, kg/L	0.860
Colour	Red
Kinematic Viscosity at 40°C, cSt	41.5
Kinematic Viscosity at 100°C, cSt	7.25
Viscosity Index	140
Zinc, %wt	0.10

NOTE: Values stated herein are typical and do not represent a specification.